



MT4

Mains Fed • Counter-top • Hot Water Boiler



trial it, love it, keep it!

Request your no obligation 10 day trial

Call **01392 877172** Email **hello@thirstywork.com**

www.thirstywork.com/free-trial

MT4

Counter top model with sleek temperature display



KEY FEATURES

- ✓ Designed to save time, energy and money
- ✓ Uninterrupted hot water supply
- ✓ Ideal for making up to 156 cups per hour
- ✓ Up to 4 litres per serving
- ✓ Space saving model
- ✓ Insulated tank for energy-efficiency
- ✓ LED temperature display
- ✓ Removeable drip tray
- ✓ Easy to clean
- ✓ Full filter change and servicing package
- ✓ With **pura** filtration

COLOUR OPTIONS



Stainless Steel

WATER OPTIONS



Hot

INSTALLATION OPTIONS



Counter-top Unit

The MT4 is an energy efficient and reliable counter top water boiler, suitable for locations where space is limited. The sleek temperature display helps you to ensure that your water is kept at a constant temperature, ready for use. The MT4 is the boiling water solution for small to medium sized catering establishments, canteens, and staff rooms, dispensing 28 litres per hour of hot water for up to 156 cups of tea or coffee.

DIMENSIONS

Height:	464mm
Width:	202mm
Depth (inc. drip tray):	436mm

FULL SPECIFICATION MT4 counter top hot water boiler

Type	Counter top - standard range
CAPACITY, WEIGHTS AND DIMENSIONS	
Capacity	28 litres
Unit dimensions	202mm (w) x 436mm (d) x 589mm (h) (depth includes drip-tray)
Packed dimensions	510mm (w) x 260mm (d) x 655mm (h)
Tap to drip tray	238mm
Packed weight	9.5kg
CONSTRUCTION	
Outer fabrication (body) construction	Stainless steel surround and acrylic front
Tank construction	Stainless steel 304L
Drip-tray construction	Plastic
ELECTRICAL	
Power rating	2.8kW
Voltage supply	2.8kW @200V
Electrical supply	Single-phase, N and E (13A)
Plug type	UK standard 3-pin
Fitted cable length	1m
PLUMBING	
Water inlet connection	3/4" BSP
Food quality, flexible mains water hose	1.1m PTFE hose with 3/4BSP connection
Mains water pressure required (limits):	100-500kPa, 0.1-0.5MPa (14.5-72.5psi)
Overflow/waste connection	Front via removable drip-tray
PERFORMANCE	
Water temperature delivered	95°C (default) – can be adjusted if required
Heat up time to working temperature	40 mins (full tank capacity)
Output per hour (@ default temperature setting)	28 litres
Rapid draw-off	4 litres
FILTRATION	
Taste and odour, sediment and reduces lime-scale	Yes
Filter benefits	Removes trace plastics in water down to 10 micron size
Max filter capacity	Up to 3,006 litres
OTHER FEATURES	
Insulated tank for minimal energy-loss	Yes
Over-boil and boil-dry protection	Yes fitted as standard
STANDARDS AND APPROVALS	
UL and NSF approved	Yes
CE Certified	Yes

trial it, love it, keep it!

Request your no obligation 10 day trial

Call **01392 877172** Email **hello@thirstywork.com**

www.thirstywork.com/free-trial