



WA5N

Mains Fed • Wall Mounted • Hot Water Boiler



trial it, love it, keep it!

Request your no obligation 10 day trial

Call **01392 877172** Email **hello@thirstywork.com**

www.thirstywork.com/free-trial

WA5N

Wall Mounted Hot Water Boiler



KEY FEATURES

- ✓ Designed to save time, energy and money
- ✓ Wall mounted
- ✓ Ideal for up to 10 users
- ✓ Easy to clean
- ✓ 5 litre immediate draw off
- ✓ Large heavy duty non-drip tap
- ✓ Full filter change and servicing programme included
- ✓ With **pura** filtration

COLOUR OPTIONS



Stainless Steel

WATER OPTIONS



Hot

INSTALLATION OPTIONS



Wall mounted

The WA5N is our 5 litre wall mounted boiler, ideal for customers who are working to a budget and want a compact, quality hot water boiler with slightly lower specification.

DIMENSIONS

Height:	432mm
Width:	290mm
Depth:	205mm

FULL SPECIFICATION WA5N wall mounted hot water boiler

Type	Economy Wall Mount
Country of design and manufacture	UK
CAPACITY, WEIGHTS AND DIMENSIONS	
Capacity	5 litres
Unit dimensions	290mm (w) x 205mm (d) x 432mm (h)
Packed dimensions (W x D x H)	285mm (w) x 380mm (d) x 540mm (h)
Tap clearance	85mm
Product weight - empty	7.8kg
Product weight - full	16.0kg
Packed weight	9.1kg
CONSTRUCTION	
Outer fabrication (body) construction	304 grade stainless steel (mirror polish)
Tank construction	304 and 316 grade stainless steel
Tank wall thickness	0.9mm
ELECTRICAL	
Power rating	3kW
Voltage supply	230 V (50-60Hz)
Electrical supply	Single-phase, N and E (13A)
Electrical Connection	Wire into double-pole fused spare (minimum cable size: 1.5mm ²). Use of an ELCB is recommended
PLUMBING	
Water inlet connection	3/4" BSP or 15mm push-fit
Mains water pressure range	2 - 7 bar (28psi - 100psi)
Overflow/waste connection	15mm push-fit (extend if required: pipework to have a continuous fall (no longer than 500mm), no more than 3 right-angle bends
PERFORMANCE	
Water temperature delivered	96°C (default) – can be adjusted if required
Heat up time to working temperature	16 mins (full tank capacity)
Output per hour (@ default temperature setting)	27 litres (higher output/hour if set @ lower temperature)
Rapid draw-off	5 litres
Recovery per minute	0.5 litres
Stand-by power loss (idle mode)	0.1 kW/h
FILTRATION	
Taste and odour, sediment and reduces lime-scale	No (available as an optional extra if required)
Filter benefits	Removes trace plastics in water down to 10 micron size
Max filter capacity	Up to 3,006 litres
OTHER FEATURES	
Tank-baffle plates – unique design aids heat recovery and reduces steam emissions to atmosphere	Yes
Early warning lime-scale diagnostics (via LED light)	Yes - Basic
Dual safety protection	Yes - over-boil and boil-dry protection
STANDARDS AND APPROVALS	
WRAS approved	Yes
EMC Tested and Certified (EN 55014 and EN 61000)	Yes
Electrical Safety Tested and Certified to BS standard EN 60335-1 and 2	Yes

Request your no obligation 10 day trial
 Call **01392 877172** Email **hello@thirstywork.com**
www.thirstywork.com/free-trial