



pura6000 commercial filter

Ion Exchange filter for prevention of limescale, ideal for use in cafés and restaurants, hot water boilers and coffee machines

pura6000

- ✓ Mixed blend of ION exchange resin
- ✓ Removes trace plastics in water down to 10 micron size
- ✓ Reduces scale and removes chlorine content, bad taste and odour issues
- ✓ 30% fixed bypass
- ✓ Capacity of 6,002 litres
- ✓ Retains trace minerals
- ✓ Keeps pH levels stable
- ✓ Protects machines
- ✓ Auto water shut off
- ✓ Easy install / change

SPECIFICATION

Height:	380mm
Width:	150mm
Depth:	150mm
Flow rate:	0.26 gpm (1L / min) at 60 psi
Pressure range:	30 - 100 psi
Max temperature:	35 - 100°F (2 - 38°C)
Service life:	6 - 12 months
Capacity:	Up to 6,002 litres
Micron rating:	10 micron
Inlet / outlet size:	3/8 inch push fit connectors

pura6000 filtered water produces a consistently better tasting tea/coffee, by stabilising pH levels to ensure the best tasting filtered water with every cup.

pura6000 ION Exchange Resin filters incorporate a mixed blend of media to reduce scale build up, preventing costly machine repairs. These filters can be used in a wide variety of applications including hot water boilers, hot liquid vending and espresso machines in catering establishments.

Reduction
of chlorine,
taste and
odour

High level
of scale
reduction

Removes
trace
plastics



Call **01392 877 172** Email **hello@thirstywork.com**
www.thirstywork.com

pura is part of the thirsty work family of companies. The data here is to be understood as an approximate.