



E6-C NHS Mains Fed Watercooler

Mains Fed • Counter-top • Chilled • Filtered



NHS
approved,
with UV-C
purification

Optional
touchless
dispense

trial it, love it, keep it!

Request your no obligation 10 day trial

Call **01392 877 172** Email **hello@thirstywork.com**
thirstywork.com/free-trial



hydrateconsciously!
We're committed to reducing plastic waste

E6-C mains fed watercooler

Chilled only model, designed for infection control

KEY FEATURES

- ✓ Chilled only
- ✓ Designed for the NHS and healthcare
- ✓ Ultra-hygienic, back-lit touch-sensitive control panel, with antimicrobial protection
- ✓ Hygienic single water pathway
- ✓ Chemical-free and energy-efficient LED-UV-C water purification
- ✓ Optional touchless operation via Bluetooth® app or Sensorbeam® Cabinet
- ✓ 290mm dispense height
- ✓ Energy-saving Dry Chill® cooling system
- ✓ Optional internal alarmed waste kit
- ✓ Full filter change and servicing package included
- ✓ With **pura** filtration
- ✓ Built in the UK



COLOUR OPTIONS



Black



Silver

WATER OPTIONS



Chilled



Filtered

Not all options are included as standard, please choose at point of order

INSTALLATION OPTIONS



Counter-top Unit

The Borg and Overstrom E6-C NHS water cooler dispenser offers unparalleled infection control for drinking water, mitigating the risk of bacteria and virus transmission. It has been designed to meet stringent water quality standards for the NHS and healthcare sector, through a unique single water pathway, UV-C purification, Pura filtration and optional hygienic touch-free dispense.

The short, single water pathway eliminates the risk of standing water where bacteria may harbour, reducing the risk of pseudomonas and Legionella.

The E6-C NHS water cooler combines intelligent eco-friendly technology, energy-efficiency, powerful performance and ultimate hygiene protection to ensure the safety and hygiene of dispensed water.

DIMENSIONS

Height:	420mm
Width:	320mm
Depth:	460mm
Dispense height:	290mm

FULL SPECIFICATION E6-C NHS mains fed counter-top watercooler

Power requirements	Hertz 50 / Volts 230-240	
Max power consumption	Chilled	140W
Direct chill temperature	Min 2°C / Max 11°C	
Throughput litres per hour	Chilled	50L/h
Dimensions	320mm (W) x 460mm (D) x 420mm (H)	
	Dispense height	290mm

AVAILABLE ACCESSORIES

 Plastic-free
Recycle me!



Recyclable Paper Cups

- 7oz recyclable paper cups
- 4oz paper cones



Touchless Dispense Foot Control and App

Control your water dispenser with foot control. The SensorBeam™ Base cabinet is an innovative, illuminated floorstanding base with projection touchless dispense, or a smartphone app, eliminating the risk of spreading bacteria on touch-panels.



Please contact us to check model compatibility and to activate this feature on your dispenser



T-Safe Filter Kit

Primarily for healthcare environments, this added layer of protection can be installed at the point of dispense to capture any potential bacteria, waterborne pathogens or other contaminants.

trial it, love it, keep it!

Request your no obligation 10 day trial

Call **01392 877 172** Email **hello@thirstywork.com**
thirstywork.com/free-trial