



**thirstywork**  
*we're all about water!*

1000-M

Mains Fed • Counter-top • Hot Water Boiler



Our boilers are protected with **puraguard** to prevent the growth of bacteria and virus

*trial it, love it, keep it!*

Request your no obligation 10 day trial

Call **01392 877172** Email **hello@thirstywork.com**

**www.thirstywork.com/free-trial**

# 1000-M

Space saving counter top model



## COLOUR OPTIONS



Stainless Steel

## WATER OPTIONS



Hot

## INSTALLATION OPTIONS



Counter-top Unit

## KEY FEATURES

- Designed to save time, energy and money
- Uninterrupted hot water supply
- Great entry level machine
- Only requires 13 amp plug socket
- Easy to clean
- Full filter change and servicing package included
- With **pura** filtration
- Comes with **puraguard** Antibacterial and antiviral protection

The 1000-M model is designed for locations where space is very limited and is ideal for customers who are trying to fit a water boiler on a worktop or below wall cupboards.



All of our boilers are treated with Puraguard - a ground-breaking protective antimicrobial coating that's applied to your dispensers taps, providing 24hr protection against the growth of microbes (bacteria, moulds, fungi and viruses). Ask us for more information on this protective coating.

## DIMENSIONS

Height:	400mm
Width:	218mm
Depth (inc. drip tray):	465mm

## FULL SPECIFICATION 1000-M counter top hot water boiler

Type	Counter top - standard range
Country of design and manufacture	UK
<b>CAPACITY, WEIGHTS AND DIMENSIONS</b>	
Capacity	5 litres
Unit dimensions	218mm (w) x 465mm (d) x 400mm (h) (depth includes drip-tray)
Packed dimensions	335mm (w) x 560mm (d) x 650mm (h)
Tap clearance	150mm
Product weight - empty	9.7kg
Product weight - full	16.0kg
Packed weight	12.0kg
<b>CONSTRUCTION</b>	
Outer fabrication (body) construction	304 grade stainless steel (superbrush polish)
Tank construction	304 and 316 grade stainless steel
Tank wall thickness	0.9mm
Drip-tray	304 grade stainless steel - (mirror polish)
<b>ELECTRICAL</b>	
Power rating	3kW
Voltage supply	230 V (50-60Hz)
Electrical supply	Single-phase, N and E (13A)
Plug type	UK standard 3-pin
Fitted cable length	1.7m
<b>PLUMBING</b>	
Water inlet connection	3/4" BSP
Food quality, flexible mains water hose	1.6 metre long, (3/4"BSP)
Mains water pressure range	2 - 7 bar (28psi - 100psi)
Overflow/waste connection	Choice of front (via drip-tray) (or rear using kit not supplied)
<b>PERFORMANCE</b>	
Water temperature delivered	96°C (default) - can be adjusted if required
Heat up time to working temperature	15 mins (full tank capacity)
Output per hour (@ default temperature setting)	28 litres (higher output/hour if set @ lower temperature)
Rapid draw-off	5 litres
Recovery per minute	0.5 litres
Stand-by power loss (idle mode)	0.066 kW/h
<b>FILTRATION</b>	
Taste and odour, sediment and reduces lime-scale	Yes
Filter benefits	Removes trace plastics in water down to 10 micron size
Max filter capacity	Up to 3,006 litres
<b>OTHER FEATURES</b>	
Tank-baffle plates - unique design aids heat recovery and reduces steam emissions to atmosphere	Yes
7 day programmable timer	No
Energy-saving ECO mode	No
Early warning lime-scale diagnostics (via LED light)	Yes - basic
Dual safety protection	Yes - over-boil and boil-dry protection
<b>STANDARDS AND APPROVALS</b>	
WRAS approved	Yes
EMC Tested and Certified (EN 55014 and EN 61000)	Yes
Electrical Safety Tested and Certified to BS standard EN 60335-1 and 2	Yes